

FRANK PATTERN™ AREA DRAINS 20C, 30C, 40C

SPECIFICATION

Recommended for use on concrete floors to facilitate drainage where water can collect. Drain unit consists of cast iron main body and grate. Assembly is secured to pipe using Instant Set® clamp with stainless steel fasteners.

DESIGN FEATURES

- Cast iron main body and grate assembly with corrosion resistant coating
- Instant Set® drain pipe attachment. No additional hardware required
- Removable grate for drain cleaning and replacement
- Stainless steel fasteners with stainless steel & neoprene washers

INSTALLATION

1. Position drain assembly in place with drain pipe connected prior to pouring concrete.
2. Instant Set® joint clamps on outside of drain pipe. Remove grate and simply slide over pipe. Evenly tighten 3 internal bolts with rubber washer seals, torque to 20 inch-pounds. Re-install grate.
3. Pour concrete flooring to level of grate.

COMPLIANCES/LISTINGS

- IAPMO 0848; ASME A112.6.3-2019 / UPC / IPC




30C

PART NUMBER	OUTLET SIZE	OUTLET TYPE	ROUND STRAINER	MSTR CTN QTY
20C	2"	Instant Set®	6"	1
30C	3"	Instant Set®	7"	1
40C	4"	Instant Set®	8"	1

Dimensions

Top View

Side View



PART NUMBER	NOMINAL PIPE CONNECTION	DIMENSIONS (inches)			
		A	B	C Area	D
20C	2"	3 5/8	4 3/8	7.21 sq. in.	1 15/16
30C	3"	4 5/8	4 1/4	9.26 sq. in.	1 15/16
40C	4"	5 1/2	4 1/8	14.24 sq. in.	1 15/16

Product Submittal	
Job Name:	Date:
Part Number:	Quantity:
Architect:	
Contractor:	

Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained. 4/2021