

## FRANK PATTERN™ CLEANOUTS & FLOOR ACCESS COVERS

### SPECIFICATION

For Use with underground drain pipe access.  
Recommended for concrete floors.

### DESIGN FEATURES

- Coated cast iron main body with brass cover plate and ring
- Stainless steel fasteners

### COMPLIANCES/LISTINGS

- IAPMO 4191; ASME A112.36.2M - 1991/UPC/IPC
- Compliant to Uniform Plumbing Code (UPC®)
- Compliant to International Plumbing Code (IPC®)

### INSTALLATION

1. Secure to drain pipe at desired height using 3 set screws.
2. Install to pipe cleanout prior to concrete pour.
3. Pour concrete flooring to top of brass ring.





N404W/4440



4440

### Dimensions



#### CLEANOUTS WITH FLOOR ACCESS COVER

PART NUMBER	OUTLET SIZE	OUTLET TYPE	MSTR CTN QTY	DIMENSIONS (inches)			
				A	B (min)	B (max)	C
N404W/4440	4"	No-Hub	4	5 1/16	4 1/8	5 1/4	4 1/4
N404	4"	No-Hub, Body Only	4	-	4 1/8	5 1/4	4 1/4

#### FLUSH FLOOR CLEANOUTS

PART NUMBER	MATERIAL	PIPE SIZE	MSTR CTN QTY
4430	Iron/Brass	2" - 3"	6
4440	Iron/Brass	3" - 4"	6

Product Submittal	
Job Name:	Date:
Part Number:	Quantity:
Architect:	
Contractor:	

Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained. 4/2021