

MINI-HAMMER ARRESTORS



DESIGN FEATURES

- Machined fittings for superior quality
- Spun copper end cap for clean, attractive look
- Eliminates water hammer problems and ensures a safer, quieter residential plumbing system
- Ideal for repair/remodel and retrofit upgrades
- AA Hammer Arrestors
- Hammer Arrestors will function when installed in any orientation (Horizontal, Vertical, etc.)
- No access panel needed
- Install within six feet of the fixture for best performance

OPERATING SPECIFICATIONS

- Operating Temperature 40°F-160°F
- Operating Pressure 20-180 PSI

COMPLIANCES/LISTINGS

- Listed and certified to ASSE 1010 through IAPMO, file number 4541
- Lead Free. Listed through IAPMO, File # 6545
- NSF/ANSI 61 listed through IAPMO File #N-6614



NSF/ANSI 61
ASSE 1010



Lead Free Compliant

Part Number	Description	MSTR CTN QTY
P-06393	3/8" Crimp PEX tee	50
P-06398	5/8" O.D. Compression tee	50
P-09399	Mini HA, FGHT Swivel x MGHT, Elbow	50
P-06402	1/2" FEM Sweat x 1/2" Male Sweat	50
P-09719	Mini HA, 1/2" Male CPVC, Straight	50
P-09729	Mini HA, 1/2" Crimp PEX, Straight	50
P-09739	Mini HA, 1/2" UPONOR ProPEX®, Straight	50
P-09749	Mini HA, 1/2" Male Copper Sweat, Straight	50
P-09759	Mini HA, 3/4" Female Copper Sweat, Straight	50
P-09769	Mini HA, 1/2" Female Copper Sweat, Straight	50
P-09799	Mini HA, 1/2" Everloc+ PEX, Straight	50
P-09829	Mini HA, 1/2" Crimp PEX F1807, Tee	50
P-09839	Mini HA, 1/2" UPONOR ProPEX® F1960, Tee	50
P-09849	Mini HA, 1/4" O.D. Compression, Tee	50
P-09859	Mini HA, 3/8" O.D. Compression, Tee	50
P-09869	Mini HA, 3/8" O.D. Compression x 3/8" Female O.D. Compression, Tee	50
P-09879	Mini HA, 5/8" O.D. Compression x 5/8" Female O.D. Compression, Tee	50
P-09899	Mini HA, 1/2" Rehau PEX, Tee	50

Product Submittal	
Job Name:	Date:
Part Number:	Quantity:
Architect:	
Contractor:	

Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained. Rev B 2/2021