



QUARTER TURN BALL VALVES Specification Sheet

DESIGN FEATURES

- Quick and easy quarter-turn shut-off.
- Heavy duty nickel plated brass ensures durability.
- Ball style valve will not freeze up.
- Teflon seats for extra wear resistance.
- Chloramine/chlorine resistant O-rings will not break down due to oxidation.
- One-year limited warranty.
- Innovate connection designs that eliminate additional leak paths.
- Bulk Packaged in quantities of 144 units per case.

MATERIAL SPECIFICATIONS

- Working Pressure: 20psi-125psi with intermittent impulse up to 180psi.
- Operating Temperature: 40°F-160°F with intermittent temperatures up to 180°F.
- Bodies, & Nuts - Nickel Plated Brass
- O-Rings/Washers - NSF/ANSI 61 Compliant chlorine/chloramine resistant NBR or EPDM.

NICKEL-PLATED VALVES				
LOW LEAD ANGLE VALVE PART NUMBER	LOW LEAD STRAIGHT VALVE PART NUMBER	INLET	OUTLET	LIMITED AVAILABILITY NON-LOW LEAD EQUIV. PART NUMBER
V-001-A-LL	N/A	5/8" O.D. Compr.	1/4" O.D. Compr.	V-001-A
V-100-A-LL	V-100-S-LL	1/2" Sweat	3/8" O.D. Compr.	V-100-S
V-101-A-LL	V-101-S-LL	5/8" O.D. Compr.	3/8" O.D. Compr.	V-101-S
V-102-A-LL	V-102-S-LL	1/2" FIP	3/8" O.D. Compr.	V-102-S
V-103-A-LL	V-103-S-LL	1/2" Crimp PEX ASTM F1807	3/8" O.D. Compr.	N/A
V-104-A-LL	V-104-S-LL	1/2" Uponor PEX ASTM F1960	3/8" O.D. Compr.	V-104-A V-104-S
V-105-A-LL	V-105-S-LL	3/8" FIP	3/8" O.D. Compr.	V-105-S
V-107-A-LL	N/A	1/2" FIP	3/4" Hose Thread	N/A
V-401-A-LL	V-401-S-LL	5/8" O.D. Compr.	1/2" OR 7/16" Slip Joint	V-401-A V-401-S
V-402-A-LL	V-402-S-LL	1/2" FIP	1/2" OR 7/16" Slip Joint	V-402-S
V-500-A-LL	V-500-S-LL	1/2" Female CPVC ASTM D2846	3/8" O.D. Compr.	N/A
N/A	V-2000-S-LL	3/8" O.D. Female Compr. H.C.	3/8" O.D. Compr.	N/A



MISCELLANIOUS VALVES (Non-Low Lead)			
PART NUMBER	ADDTL. DESCRIPTION	INLET	OUTLET
V-750-S	Polished Brass HoseMate Valve Brass Handle	3/4" F.G.H.T.	3/4" M.G.H.T.
P-06306	Polished Brass HoseMate Valve Blue Handle	5/8" O.D. Compr.	3/4" M.G.H.T.
P-06307	Polished Brass HoseMate Valve Red Handle	5/8" O.D. Compr.	3/4" M.G.H.T.

COMPLIANCES/LISTINGS

- Low Lead Models ("LL" P/Ns) are IAPMO listed Lead Free Compliant File No. 6545
- IAPMO listed to NSF/ANSI 61 File No. N-6614
- IAPMO listed to ASME A112.18.1/CSA B125.1 File No. 4577



3689 Arrowhead Drive, Carson City, NV 89706
 Phone (800) 854-3215 Fax (800) 243-1777
 E-mail sales@lspproducts.com
 Website www.lspproducts.com
 Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained.

Product Submittal	
Job Name:	
Date:	
Part Number	Quantity
Architect:	
Contractor:	