

ULTRACORE™ LARGE DIAMETER CONNECTORS



DESIGN FEATURES

- Chloramine resistant washers
- Exclusive POWR-TIGHT 12 point crimp - many times industry standard
- Withstands dramatic changes in water pressure
- Easy installation, no special tools or soldering required

OPERATING SPECIFICATIONS

- Working Temperature: 40°F-160°F with intermittent temps up to 180°F
- Working Pressure: 20-125 PSI with intermittent impulse up to 180 PSI

MATERIAL SPECIFICATIONS

- Tubing: LSP's Patented UltraCore™
- End Fittings: Brass
- Connection Nuts: Nickel Plated Brass
- Washers- NSF/ANSI 61 Compliant

COMPLIANCES/LISTINGS

	LISTING	STANDARD/COMPLIANCE
1	IAPMO 2111	ASME A112.18.6-2017/CSA B125.6-17
2	IAPMO 6545	NSF / ANSI 372 - 2016
3	IAPMO N-6614	NSF / ANSI / CAN 61 - 2018

✓ Lead Free NSF/ANSI 61



PART NUMBER	LENGTH	MSTR CTN QTY	LISTINGS
LEAD FREE NICKEL PLATED OVER BRASS FITTINGS			
1/2" F.I.P. w/ WASHER X 1/2" F.I.P w/ WASHER			
PPC-118-PP	18"	10	1, 2
PPC-124-PP	24"	10	1, 2
LEAD FREE NICKEL PLATED OVER STEEL FITTINGS			
1" F.I.P. w/ WASHER X 1" F.I.P. w/ WASHER			
SFF-10012	12"	40	1, 2, 3
SFF-10018	18"	40	1, 2, 3
SFF-10024	24"	40	1, 2, 3
SFF-10036	36"	40	1, 2, 3

Product Submittal	
Job Name:	Date:
Part Number:	Quantity:
Architect:	
Contractor:	

Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained. 4/2021