

ULTRACORE™ & MIGHTYFLEX™ WASHING MACHINE CONNECTORS

DESIGN FEATURES

- Chloramine resistant washers
- Exclusive POWR-TIGHT 12 point crimp
- Chloramine resistant tubing
- Withstands dramatic changes in water pressure
- Easy installation, no special tools required

MATERIAL SPECIFICATIONS

- Working Pressure: 160 psi
- Operating Temperature: 33° F - 140° F
- Tubing: UltraCore
- Nuts & End Fittings: Brass
- Washers: NSF/ANSI 61 Compliant

COMPLIANCES/LISTINGS

LISTING		STANDARD/COMPLIANCE
IAPMO	2111	ASME A112.18.6-2017/CSA B125.6-17
IAPMO	N-6614	NSF / ANSI / CAN 61 - 2018



ULTRACORE™ POLYMER BRAIDED WASHING MACHINE CONNECTORS

PART NUMBER	LENGTH	MSTR CTN QTY
1/2" I.D. – 3/4" F.G.H.T. X 3/4" F.G.H.T. – FOR FRONT LOAD WASHERS		
WAS-148-PP	48"	10
WAS-160-PP	60"	10
WAS-172-PP	72"	10
WAS-174-B	74"	10
WAS-196-B	96"	10

MIGHTYFLEX™ CONNECTORS

3/8" I.D. – 3/4" F.G.H.T. X 3/4" F.G.H.T. – FOR TOP LOAD WASHERS		
WAS-348-PP	48"	10
WAS-360-PP	60"	10
WAS-372-PP	72"	10
3/8" I.D. – 3/4" F.G.H.T. X 90° 3/4" F.G.H.T.		
WAS-448-PP	48"	10
WAS-460-PP	60"	10
WAS-472-PP	72"	10
WAS-496-PP	96"	10

Product Submittal	
Job Name:	Date:
Part Number:	Quantity:
Architect:	
Contractor:	

Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained. 4/2021