

WATER HEATER PAN



Water Heater Pan – Plastic



Water Heater Pan – Undrilled

DESIGN FEATURES

- Protects against water damaged caused when water heaters start leaking
- Simple to install - just set water heater into pan when installing
- Will not rust or corrode
- Round design enables pan to be installed in small areas
- Made in North America

SPECIFICATIONS

- Thermoformed parts constructed of high impact polystyrene
- Thickness of material to be 0.050"
- Color: Black
- Standard side outlet hole (unless specified).
- Comes with 1" male adapter, gasket and locknut
- All pans are 2-1/2" in depth to meet code requirements

Part Number	Description	Master CTN QTY
Drilled		
WHP20-1D	20" I.D. Drilled	20
WHP22-1D	22" I.D. Drilled	20
WHP24-1D	24" I.D. Drilled	20
WHP26-1D	26" I.D. Drilled	20
WHP28-1D	28" I.D. Drilled	20
Undrilled		
WHP20-1U	20" I.D. Undrilled	20
WHP22-1U	22" I.D. Undrilled	20
WHP24-1U	24" I.D. Undrilled	20
WHP26-1U	26" I.D. Undrilled	20
WHP28-1U	28" I.D. Undrilled	20
WHP30-1U	30" I.D. Undrilled	6
Adapter		
SPF-100	1" Adapter	1

Physical Property Summary			
Property	Test Method	Value	Unit
Specific Gravity	ASTM D-792	1.04	g/cc
Tensile Modulus	ASTM D-638	250,000	psi
Tensile Strength @ Yield	ASTM D-638	4,000	psi
Flexural Modulus	ASTM D-790	370,000	psi
Flexural Strength @ Yield	ASTM D-790	8,200	psi
Izod Impact	ASTM D-256 (73°F)	2.0	ft-lbs/in
Falling Dart Impact	ASTM D-3029(G) (73°F)	85	in-lbs
Heat Deflection Temperature	ASTM D-648 (264 psi, unannealed)	165	°F
Coefficient of Thermal Expansion	ASTM D-696	4.5 x 10 ⁻⁵	in/in/°F
Hardness	ASTM D-785	68	Rockwell "L"
Flammability	UL Subject 94	HB	0.062"
Gardner Gloss	ASTM D-523	70	%

Product Submittal	
Job Name:	Date:
Part Number:	Quantity:
Architect:	
Contractor:	

Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained. Rev 1 10/2021