

## Value Engineered QUARTER TURN BALL VALVES

### Material Specifications

- Value engineered and nickel plated
- Working pressure: 20psi-125psi with intermittent impulse up to 180psi
- Operating temperature: 40°F-160°F with intermittent temperatures up to 180°F
- O-Rings/Washers – NSF/ANSI 61 compliant chlorine/chloramine resistant NBR or EPDM

### Design Features

- Quick & easy quarter turn shut off
- Value engineered nickel plated brass ensures durability at optimized value
- Ball style valve will not freeze up
- PTFE seats for extra wear resistance
- Chloramine/chlorine resistant o-rings will not break down due to oxidation
- 3/8" compression nut & ferrule sold separately if needed (P-06706)
- One year limited warranty
- Innovative connection designed to eliminate additional leak paths



### Compliance/Listings

- IAPMO listed Lead Free Compliant File No. 6545
- IAPMO listed to NSF/ANSI 61 File No. N-6614
- IAPMO listed to ASME A112.18.1/CSA B125.1 File No. 4577

ASME A112.18.1/CSA B125.1



ANGLE VALVE P/N	STRAIGHT VALVE P/N	INLET	OUTLET	BAG QTY	CARTON QTY
VE-101-A-LL	VE-101-S-LL	5/8" O.D. COMPR.	3/8" O.D. COMPR.	30	180
VE-103-A-LL	VE-103-S-LL	1/2" CRIMP PEX	3/8" O.D. COMPR.	30	180
VE-104-A-LL	VE-104-S-LL	1/2" UPONOR PEX	3/8" O.D. COMPR.	30	180
VE-500-A-LL	—	1/2" CPVC	3/8" O.D. COMPR.	30	180

\*Bag Quantities = Order Multiples

### ACCESSORIES

P/N	DESCRIPTION	BAG QTY	CARTON QTY
P-06706	Bag of 30 3/8" OD Comp Nut and Ferrules	*1 Bag of 30 Nuts and Ferrules	10 Bags of 30 Nuts and Ferrules
P-06735	Tee adapter, Female 3/8" Comp x 2 x Male 3/8" Comp	N/A	100 pcs

\*Order for 1 piece of P-06706 = 1 Bag containing Compression Nuts and Ferrules

Product Submittal	
Job Name:	Date:
Part Number:	Quantity:
Architect:	
Contractor:	

Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained. Rev A 04/2021